

PW3-S6-3/4M

SA Multiple Tenancy Range



IP23

Enclosure Range

Technical Specifications

Code	Occupancy	Width	Height	Depth	Panel Size
PW3-S6-3/4M	Up to 4 Meter	700mm	1125mm	325mm	500x825mm
Earth & Neutral Bar Assembly		▶ 6 x 25mm ² Earth		▶ 1 x 10mm ² / 6 x 25mm ² Neutral	
Pre-wired 0.6/1KV TCW LSHF Flex		<ul style="list-style-type: none"> ▶ Active - 16mm² (Red / White / Blue) ▶ Neutral - 10mm² (Black) ▶ Meter Neutral - 6mm² (Black) 			

PW3-S2-M2 Feature & Benefits

Suitable for up to 4 x Three Phase meters

Accepted by ETSA Utilities & SA Power Networks

IP23 Rated meter enclosure

Galvanised steel construction Powder Coated Light Grey (RAL 7035)

Designed to AS/NZS 3000:2018 requirements

24 Module full DIN

Panel Isolator: up to 125 AMP, 3 Phase, 10KA

Meter Isolator: 63 AMP, 3 Phase

Service Neutral Link 1 x 16mm² / 1 x 25mm² / 1 x 70mm²

Cable tie off point / Door open catch / Door cable protector

ETSA Utilities / SAPN Compliant door lock & two keys

Door open strap for easy installation & maintenance

KEY FEATURES

- ▶ Pre-wired up to 4x3 Phase Meter
- ▶ SA Power Network Approved
- ▶ Designed to meet AS3000 Standard
- ▶ Door Lock suits SAPN/ETSA requirements
- ▶ Plinth and Rain Hood available

