

MES4

Meter Enclosure - Multiple Tenancy
SA Type 4



IP23

Enclosure Range

KEY FEATURES

- ▶ SA Power Network Approved
- ▶ IP23 Protection Rating
- ▶ ETSA Utilities / SAPN Compliant door lock & two keys
- ▶ Door open strap for easy installation & maintenance
- ▶ Allowance for up to 4 x Single Phase Meters
- ▶ Pre-wired available using Australia Made Flex
- ▶ Cable Complete with Insulated end Terminals
- ▶ 150mm Depth Behind Panel
- ▶ Multiple Tenancy Application
- ▶ Powdercoat Finish (RAL7035)
- ▶ Designed to meet AS3000 Standard
- ▶ Full 24 Module DIN
- ▶ Dedicated DIN for 1 x 3 Phase Panel Isolator
- ▶ Dedicated DIN Provision for Tenancy (4x63A 6KA Meter Isolator MCB's Supplied)
- ▶ DIN Provision for Tenancy Main Switch MCB's (4x63A 6KA Consumer MCB's Supplied)
- ▶ Service Neutral Link 1 x 16mm² / 1 x 25mm² / 1 x 70mm²
- ▶ Cable tie off point / Door open catch / Door cable protector

Technical Specifications

Specifications	Width	Height	Depth
Size	700	850	325
Panel	550	550	6
Neutral Grid	2 x Ø5mm (Suits up to 10mm) 10 x Ø8mm (Suits up to 25mm)		
Earth Grid	2 x Ø5mm (Suits up to 10mm) 10 x Ø8mm (Suits up to 25mm)		
Mains Neutral	1 x Ø5.5mm; 1 x Ø7mm; 2 x Ø9mm; 1 x 9mm x 9mm (Suits 75mm)		

Product	Order Code	Meter Isolator	DIN	Panel Isolator	Quantity
SA Type 4	MES4	(N)	24-Pole	(N)	1
SA Type 4 MI	MES4MI	4x1Phase 63A 6kA	24-Pole	1 x 3 Phase 63A 6kA	1

Available Accessories

Accessory/Spare Parts	Order Code	Description	Quantity
SA Type Plinth (Suits SA Type 6)	PLS4-75	▶ SA Type 4 Plinth 3mm Steel 750(H) 700(W) 325(D)	1
SA Type 4 Door - With Lock	DRS4L	▶ STD SA Type 4 Replacement Hinged Door	1
Door Lock	DRL-G	▶ Keyed to SAPN & ETSA Standard	1
Spare Part - SA Type 4/3 Meter Panel	MPS4-3D	▶ SA Type 4 Hinged Meter Panel Drilled for 3 Units	1
Spare Part - SA Type 4 / 4 Meter Panel	MPS4-4D	▶ SA Type 4 Hinged Meter Panel Drilled for 4 Units	1
Spare Part - SA Type 4 Blank Meter Panel	MPS4-B	▶ Hinged Meter Panel Blank for Custom Projects	1