



IP23

Enclosure Range

KEY FEATURES

- ▶ Made to Energy NSW Specifications
- ▶ Suitable for Single Phase & Three Phase Applications
- ▶ IP23 Rated Meter Enclosure
- ▶ Cable Management Tie off Point and Lead Entry Protection AS/NZS 3000:2018
- ▶ 570 X 560 X 6mm Pre-drilled Double Hinged Meter Panel
- ▶ Door Open Strap for Easy Installation and Maintenance
- ▶ Safe 4X Ingress Protection Flanges Rear of Panel
- ▶ Panel Support Ramp for Installation Ease and Panel Sag Prevention
- ▶ 75mm Behind Meter Panel
- ▶ Knockouts Rear and Base for Convenient Cable Access
- ▶ Available with 12 or 18 Pole Surface Mount Din Rail Enclosure
- ▶ Grey RAL 7035 Powder Coat
- ▶ Wrinkle Finish Hides Brush Strokes if repainted
- ▶ Long-lasting Custom Made Australian Hinges
- ▶ Australian Moulded Plastic Safety Components
- ▶ Suitable as Construction Site Switchboard with Regulated Safety Features

Technical Specifications

Specifications	Width	Height	Depth
MAU60P	600 mm	600 mm	250 mm
Meter Panel	570 mm	560 mm	6 mm

Order Code	Name	Meter Isolator	Quantity
MAU 60P	600mm x 600mm x 250mm Single Two Meter	▶ 600mm x 600mm x 250mm Single Two Meter	24
			1

Available Accessories

Order Code	Occupancy	Width (mm)	Height (mm)	Depth (mm)	Quantity
PME12	▶ 12 Pole Surface Mount Din Rail Enclosure	160	260	60	10
PME18	▶ 18 Pole Surface Mount Din Rail Enclosure	160	365	60	10

1. All price quoted are excluding GST
 2. Sale to Wholesale customers only
 3. Price quoted include City metro delivery on all orders of \$750 or greater
 4. Orders under \$750.00 + GST, a \$70.00 delivery charge will apply