



KEY FEATURES

- ▶ Pre-wired MES6 Enclosure
- ▶ SA Power Network Approved
- ▶ Wired using Australian Made Flex Cable
- ▶ Door Lock SAPN Keyed
- ▶ Panel Isolator fitted
- ▶ Meter Isolators with Lock Off
- ▶ Sub Mains MCB
- ▶ Plinth and Rain Hood available

Technical Specifications

Specifications	Width	Height	Depth
Size	700	1125	325
Panel	550	825	6
Neutral Grid	2 x ø5mm (Suits up to 10mm) 10 x ø8mm (Suits up to 25mm)		
Earth Grid	2 x ø5mm (Suits up to 10mm) 10 x ø8mm (Suits up to 25mm)		
Mains Neutral	1 x ø5.5mm; 1 x ø7mm; 2 x ø9mm; 1 x 9mm x 9mm (Suits 75mm)		

Available Accessories

Order Code	Name	Description	Quantity
PLS4-75	SA Type 4 Plinth (Suits SA Type 6)	▶ SA Type 4 Plinth 3mm Steel 750(H) 700(W) 325(D)	1
DRS6L	SA Type 4 Door - With Lock	▶ STD SA Type 6 Replacement Hinged Door	1
DRL-G	Door Lock	▶ Keyed to SAPN & ETSA Standard	1
MPS6-6D	Spare Part- SA Type 6 / 6 Meter Panel	▶ SA Type 6 Hinged Meter Panel Drilled for 6 Units	1
MPS6-B	Spare Part- SA Type 6 Blank Meter Panel	▶ Hinged Meter Panel Blank for Custom Projects	1

Order Code	SA Type 6 Meter Enclosure with 16mm Flex Pre-Wired	Meter Panel Isolator	Tenancy Meter Isolators	Tenancy Main Switch MCB	Quantity
PW1-S6 5M	Single Phase 5 Tenancy	3P 63A	5 x 1P 63A	5 x 1P 63A	1
PW1-S6 6M	Single Phase 6 Tenancy	3P 63A	6 x 1P 63A	6 x 1P 63A	1

1. All price quoted are excluding GST
 2. Sale to Wholesale customers only
 3. Price quoted include City metro delivery on all orders of \$750 or greater
 4. Orders under \$750.00 + GST, a \$70.00 delivery charge will apply